

Miernik Multifunctional Measurement MAS830B Mastech

kategoria: Kategorie > Mierniki - Multimeter



Kod QR:



DC Voltage 200mV/2V/20V/200V $\pm(0.5\%+3)$

600V $\pm(0.8\%+5)$

AC Voltage 200V/600V $\pm(1.2\%+10)$

DC Current 20µA/200µA/2mA/20mA $\pm(1.0\%+3)$

200mA $\pm(1.5\%+5)$

10A $\pm(3.0\%+10)$

Resistance 200Ω $\pm(0.8\%+5)$

2K Ω /20K Ω /200K Ω \pm -(0.8%+2)

2M Ω \pm -(1.0%+5)

Safety Class: I CAT II 600V

Waterproof: IP20

Fuse: F1:F250mA / 250V,F2:F 10A/250V

Power: 9V battery =, NEDA 1604 or 6F22

Maximum display value: 1999

Over-range indication: "1"

Polarity display: "□" for negative polarity

Low voltage indication: " " on the display

Operating temperature: 0~40°C(32~104°F)

Storage temperature: -10~50°C(14~122°F)

Relative humidity: <80% RH

Altitude: <2000m

Dimension (LxWxH): 144x74x40mm

Weight(no rubber case): about 160g

Weight(with rubber case): about 250g

Display: 2000 counts

Diode: 2.7V

Data hold

Low Battery Display