



Multifunctional Measurement Miernik MS8233A Mastech

kategoria: Kategorie > Mierniki - Multimeter



Kod QR:



Maximum voltage between input and the ground: CAT III 600V

Fuse protection:

F1:FF 400mA H 600V

F2:FF 10A H 600V

Power: 9V battery, NEDA 1604 or 6F22

Display: LCD 2000 counts, updates 2-3/sec

Measuring method: Dual-slope integration A/D converter

Over range indication: Only figure "1" on the display

Polarity indication: "-" displayed for negative polarity

Operating environment: 0°C to 40°C

Storage temperature: -10°C to 50°C

Low battery indication: " " appears on the display

Size: 140mmx67mmx30mm

Display: 2000 counts

Diode: 2.7V

Continuity Buzzer: <math><50\Omega</math>

Data hold

Low Battery Display

Weight: Approx. 112g

DC Voltage 200mV/2V/20V/200V/600V $\pm(0.5\%+3)$
AC Voltage 200V/600V $\pm(1.2\%+10)$
DC Current 20 μ A/2mA/20mA/200mA $\pm(1.0\%+3)$
10A $\pm(3.0\%+5)$
Resistance 200 Ω /2K Ω /20K Ω /200K Ω /2M Ω /20M Ω $\pm(0.8\%+4)$