



## Multiswitch 5/6 EMP-Centauri

kategoria: Kategorie > SAT technik



Kod QR:



### **MULTISWITCH 5/6 EMP-CENTAURI / SPACETRONIK PLP-3.**

PROFI CLASS is a line of products from the Czech manufacturer EMP-centauri, equipment manufactured in Europe, designed to meet the highest customer requirements. These products have an extended temperature range, and adjustable attenuation on each of the inputs.

Advantages of the PROFI CLASS:

- Extended temperature range
- All multiswitches offer input attenuators, selectable active / passive processing
- Support for Quattro and Quad LNBS
- Power switch 12V ON / OFF for terrestrial antenna preamplifier
- Compatible with DiSEqC 2.0 and below

A compact, very small multiswitch, which is used to sum terrestrial TV signals and one satellite. It has four satellite inputs. with LNB Quattro, one signal input from the dvb-t antenna, and six summed outputs. with Quattro LNB. Equipped with an additional DC 9-20V power socket that allows you to connect the power supply, e.g. to power the antenna preamplifier. External power supply is not needed in the case of passive antennas.

<b>LNB input frequency range</b>	950 - 2300 MHz
<b>Terr. Frequency range contribution</b>	5 - 862 MHz
<b>Output frequency range</b>	5 - 2300 MHz
<b>Control</b>	13/18 V + 0/22 kHz
<b>Attenuation Sat</b>	3 dB, average
<b>Suppression Terr.</b>	Average 15 dB
<b>Input isolation</b>	20 dB min
<b>Input level Sat / Terr.</b>	90/105 dBuV average
<b>Maximum output level Sat.</b>	87 dBuV average
<b>Maximum output level Terr.</b>	Average 90 dBuV
<b>Power consumption</b>	55 mA (18V)
<b>Dimensions</b>	13.5 x 10.4 x 4.1 cm
<b>Temperature range</b>	-30 .... 70 degrees C