



Miernik Digital UT501A UT-501A

category: Kategorie > Narzędzia - Tools



QR code:



FEATURES

Auto ranging

Alarm light display and buzzer

Low battery indication

LCD backlight

High voltage indication

Overload indication

TECHNICAL SPECIFICATIONS

Function Range Accuracy

Insulation Resistance Test Voltage 100 V / 250 V / 500 V / 1000 V 0%~10%

100 V 0.00 M Ω ~100 M Ω $\pm(3\%+5)$

250 V 0.00 M Ω ~99.9 M Ω $\pm(3\%+5)$

100 M Ω ~5.5 G Ω $\pm(5\%+5)$

500 V 0.00 M Ω ~99.9 M Ω $\pm(3\%+5)$

100 M Ω ~5.5 G Ω $\pm(5\%+5)$

1000 V 0.00 M Ω ~99.9 M Ω $\pm(3\%+5)$

100 M Ω ~5.5 G Ω $\pm(5\%+5)$

Load Current 50V(R=50K Ω) 1 mA 0%~10%

100V(R=100K Ω) 1 mA 0%~10%

250V(R=250K Ω) 1 mA 0%~10%

500V(R=500K Ω) 1 mA 0%~10%

1000V(R=1M Ω) 1 mA 0%~10%

Short Circuit Current < 2 mA

AC Voltage 30 V~750 V $\pm(2\%+3)$

General Characteristics

Power 6 × 1.5 V battery (R14)

Display LCD with backlight, 70.6 × 34 mm

Dimensions (H × W × D), mm 150 × 100 × 71 mm

Weight 500 g