



Multifunctional Measurement Miernik M300C Mastech

kategoria: Kategorie > Mierniki - Multimeter



Kod QR:



Maximum voltage between terminal and earth ground: CAT III 300V

Fuse protection: F 250mA/300V

Power supply: 12V battery. GP-23AX1

Display: LCD.1999 counts .update 2-3/sec

Measuring method: dual-slope integration A/D converter

Over range indication: only figure "1" on the display

Polarity indication: " - " displayed for negative polarity

Operating temperature: 0°C to 40°C(32°F to 104°F)

Storage temperature: -10°C to 50°C (10°F to 122°F)

Low battery indication: appears on the display

Size: 120x70x18mm

Weight: approx.110g

Order Ref. Number: M300CC15L

Safety Rating: CE(EMC+LVD) CATII 600V

Display: 2000 counts

Diode: 2.7V

Continuity Buzzer: <50Ω

Low Battery Display

<i>DC Voltage</i>	2V	+-(0.5%+1)
	20V/200V/300V	+-(0.8%+1)
<i>AC Voltage</i>	200V/300V	+-(1.2%+10)
<i>DC Current</i>	200mA	+-(2.0%+2)
<i>Resistance</i>	2KΩ/20KΩ/200KΩ/2MΩ	+-(1.0%+2)