

## Miernik Multifunctional Measurement MAS830B Mastech

category: Kategorie > Mierniki - Multimeter



QR code:



DC Voltage 200mV/2V/20V/200V  $\pm(0.5\%+3)$

600V  $\pm(0.8\%+5)$

AC Voltage 200V/600V  $\pm(1.2\%+10)$

DC Current 20µA/200µA/2mA/20mA  $\pm(1.0\%+3)$

200mA  $\pm(1.5\%+5)$

10A  $\pm(3.0\%+10)$

Resistance 200Ω  $\pm(0.8\%+5)$

2K $\Omega$ /20K $\Omega$ /200K $\Omega$   $\pm$ -(0.8%+2)

2M $\Omega$   $\pm$ -(1.0%+5)

*Safety Class: I CAT II 600V*

*Waterproof: IP20*

*Fuse: F1:F250mA / 250V,F2:F 10A/250V*

*Power: 9V battery =, NEDA 1604 or 6F22*

*Maximum display value: 1999*

*Over-range indication: "1"*

*Polarity display: "□" for negative polarity*

*Low voltage indication: " " on the display*

*Operating temperature: 0~40°C(32~104°F)*

*Storage temperature: -10~50°C(14~122°F)*

*Relative humidity: <80% RH*

*Altitude: <2000m*

*Dimension (LxWxH): 144x74x40mm*

*Weight(no rubber case): about 160g*

*Weight(with rubber case): about 250g*

*Display: 2000 counts*

*Diode: 2.7V*

*Data hold*

*Low Battery Display*