



## Multifunctional Measurement Miernik MS8233A Mastech

kategoria: Kategorie > Mierniki - Multimeter



Kod QR:



*Maximum voltage between input and the ground: CAT III 600V*

*Fuse protection:*

*F1:FF 400mA H 600V*

*F2:FF 10A H 600V*

*Power: 9V battery, NEDA 1604 or 6F22*

*Display: LCD 2000 counts, updates 2-3/sec*

*Measuring method: Dual-slope integration A/D converter*

*Over range indication: Only figure "1" on the display*

*Polarity indication: "-" displayed for negative polarity*

*Operating environment: 0°C to 40°C*

*Storage temperature: -10°C to 50°C*

*Low battery indication: " " appears on the display*

*Size: 140mmx67mmx30mm*

*Display: 2000 counts*

*Diode: 2.7V*

*Continuity Buzzer: <50Ω*

*Data hold*

*Low Battery Display*

*Weight: Approx. 112g*

*DC Voltage 200mV/2V/20V/200V/600V +-(0.5%+3)*

*AC Voltage 200V/600V +-(1.2%+10)*

*DC Current 20 $\mu$ A/2mA/20mA/200mA +-(1.0%+3)*

*10A +-(3.0%+5)*

*Resistance 200 $\Omega$ /2K $\Omega$ /20K $\Omega$ /200K $\Omega$ /2M $\Omega$ /20M $\Omega$  +-(0.8%+4)*